Since 1965

Chhabi Electricals Private Limited

Regd. Office & Factory : E-66, MIDC, Jalgaon - 425 003 (M.S.)
Tel : 91-257-2210626/ 27/ 28, 2270174/75, Fax : 91-257-2213434
Email : chhabi_jal@sancharnet.in, Web site : www.chhabi-india.com

CIN No : U32109MH1978PTC020807

QUALITY ASSURED COMPANY ISO:9001-2008 International Standards Certification Lic. No. QAC/R91/0100

Technical specification

Rated Maximum Power	7.4kW 230v, 1-phase 3wire (L+N+PE)
Rated Maximum current	32A
MCB Recommended	40A, 2 pole
Input cable conductor recommended size	6 sq mm 3 core cable
Input voltage	230 VAC 50Hz 1 phase (L+N+PE)
Input current	32A (Max)
Output Voltage	230 VAC ±10%, 1-phase
Output current	32A (Max)
Standby power	3W
Charging mode	RFID or CSMS enabled through OCPP
Display	In multiple options and default display as 4”3
Communication Interface	Ethernet/SIM/ WIFI
OCPP 1.6J Compliance	Yes
Safety Protection	Over current, Over voltage, Under voltage, Over temperature, Leakage, Lightning, Unconnected PE ground
Installation method	Wall mounted, Stand mounted
Charging connector	Type 2
Charging cable	5m (standard configuration)
Size (H*W*D)	400*300*210mm
Net weight	Approx 10kg
Protection level	IP55/IP67
Altitude	≤2000m
Relative humidity	5%~95%
Operating temperature	-10~55℃
Storage temperature	-40~75℃
Operating life	≥10000hrs